



Model	Color Temp.	Power Supply	Base	Rated Input Voltage	Power Consumption	Total Lumen Flux	Beam Angle	Illuminance	CRI
				(v)	(W)	(lm)	(°)	(lux-1m)	
MX30L-WW15	3000° K	Transformer	GU5.3	12V AC/DC	3W	90	15°	550Lux	85
MX30L-WW40	3000° K	Transformer	GU5.3	12V AC/DC	3W	180	40°	340Lux	70
MX30L-CW40	6500° K	Transformer	GU5.3	12V AC/DC	3W	210	40°	390Lux	70

HIGH CRI LAMP (Order Made)

Model	Color Temp.	Power Supply	Base	Rated Input Voltage	Power Consumption	Total Lumen Flux	Beam Angle	Illuminance	CRI
				(v)	(W)	(lm)	(°)	(lux-1m)	
MX30LH-WW40	3000° K	Transformer	GU5.3	12V AC/DC	3W	145	40°	260Lux	90
MX30LH-WW70	6500° K	Transformer	GU5.3	12V AC/DC	3W	170	40°	310Lux	90

- Operating Temperature : -20°C ~ 40°C
- HOUSING : ALUMINIUM

Size(mm)		Weight	IP
dia	length	(g)	
49	57	51g	30
49	56	52g	30