



Model	Color Temp.	Power Supply	Base	Rated Input Voltage	Power Consumption	Total Lumen Flux	Beam Angle	Illuminance	CRI
				(v)	(W)	(lm)	(°)	(lux-1m)	
MX50L-WW40	3000° K	Transformer	GU5.3	12V AC/DC	5W	250	40°	400Lux	70
MX50L-WW70	3000° K	Transformer	GU5.3	12V AC/DC	5W	250	70°	290Lux	70
MX50L-CW40	6500° K	Transformer	GU5.3	12V AC/DC	5W	300	40°	520Lux	70
MX50L-CW70	6500° K	Transformer	GU5.3	12V AC/DC	5W	300	70°	330Lux	70

HIGH CRI LAMP (Order Made)

Model	Color Temp.	Power Supply	Base	Rated Input Voltage	Power Consumption	Total Lumen Flux	Beam Angle	Illuminance	CRI
				(v)	(W)	(lm)	(°)	(lux-1m)	
MX50LH-WW40	3000° K	Transformer	GU5.3	12V AC/DC	5W	200	40°	350Lux	90
MX50LH-WW70	3000° K	Transformer	GU5.3	12V AC/DC	5W	200	70°	220Lux	90
MX50LH-CW40	6500° K	Transformer	GU5.3	12V AC/DC	5W	240	40°	400Lux	90
MX50LH-CW70	6500° K	Transformer	GU5.3	12V AC/DC	5W	240	70°	260Lux	90

- Operating Temperature : -20°C ~ 40°C
- HOUSING : ALUMINIUM

Size(mm)		Weight	IP
dia	length	(g)	
49	56	52g	30